Access confined spaces you never thought possible with a wheeled Toro® Dingo® compact utility loader. These models offer zero-turn capability, along with a shorter length that's easy to load on a trailer. You also get reliable hydraulic power to use a wide range of attachments. If you do a lot of tasks in tight spaces or on hard surfaces, these are the models for you.

FEATURES

4-PAW® INDEPENDENT FOUR-WHEEL DRIVE

Four independent wheel motors deliver hydraulic flow and pressure to all four wheels for improved traction and mobility. Fewer moving parts also mean less maintenance.

IMPROVED VISIBILITY

The integrated ride-on operator platform allows improved visibility of the working area and attachments.



Dingo 320-D model 22337CP

HIGHLY MANEUVERABLE

Short wheelbase design offers excellent maneuverability. Get into tight spaces where only hand labor could go before.

TORO® DINGO® WHEELED

SPECIFICATIONS

		323 WHEELED GAS (MODEL 22318)	320-D WHEELED DIESEL (MODEL 22337CP)
ENGINE	Engine	Kohler® Command 25 HP* (18.6 kw)	Kubota® D722 diesel 20.0 HP* (14.9kW)
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Air Cooled	Liquid Cooled
	Fuel Tank	11.2 gallon (42.4 liter)	4 gallon (15 liter)
	Oil Capacity	2 quarts (1.9 liter)	3.4 quarts (3.2 liter)
HYDRAULIC SYSTEM	Hydraulic Pressure	3,250 PSI (22,407 kPa)	
	Hydraulic Flow	10.8 gpm high-flow hydraulic circuit, 4 gpm low-flow hydraulic circuit	
	Reservior Capacity	17 gallons (64 liter)	14.8 gallons (56 liter)
	Track Dimensions	96.6" x 5.9" (245.3 cm x 14.9 cm)	96.6" x 9.5" (245.3 cm x 24.1 cm)
DIMENSIONS	Wheelbase	28" (71.1 cm)	
	Ground Clearance	5.8" (14.7 cm) front & rear	
Overall Dimensions (WxLxH) With Standard Tires		40.5" x 62" x 48.7" (102.8 x 157.5 x 123.7)	
Overall Dimensions (WxLxH) With Narrow Tires		35" x 62" x 48.7" (88.9 x 157.5 x 123.7)	
Maximum Operating Height		91.2" (231.6 cm)	
Hinge Pin Height		66" (167.6 cm)	
Dump Height		47" (119 cm)	
Dump Angle		34-degrees	
Reach - Fully Raised		28" (71.1 cm)	
Ground Speed		0-3.7 mph (0-6 km/h)	0-3.0 mph (0-4.8 km/h)
Weight		1,567 lbs (710.7 kg)	1,722 lbs (781.0 kg)
Tip Capacity		1,030 lbs (467.2 kg)	1,048 lbs (475.3 kg)
Rated Operating Capacity (35% of Tip Capacity)*		515 lbs (233.6 kg)	524 lbs. (237.6 kg)

*Per ISO 14397-1

