


ALT950

AL/ALT



GEHL®

| Capacities | | Metric | Imperial |
|---|-----|---|---|
| Static tipping load with forks (straight) | | 4978 kg | 10975 lb |
| Static tipping load with forks (full turn) | | 4147 kg | 9143 lb |
| Max. payload with forks as per EN 474-3 (80%) | | 3300 kg | 7275 lb |
| Max. lifting height (below forks) | h3 | 5.20 m | 17 ft 1 in |
| Max. outreach | | 3.30 m | 10 ft 10 in |
| Reach at max. height | | 1.20 m | 3 ft 11 in |
| Breakout force with bucket | | 6730 daN | 6730 daN |
| Static tipping load with pallet forks - Straight with cab | | 4978 kg | 10975 lb |
| Weight and dimensions | | | |
| Unladen weight (with forks) | | 8490 kg | 18717 lb |
| Overall length to carriage (with hitch) | l11 | 5.72 m | 18 ft 9 in |
| Wheelbase | y | 2.50 m | 8 ft 2 in |
| Overall height with cab | h17 | 2.70 m | 8 ft 10 in |
| Tilt-up angle | a4 | 9 ° | 9 ° |
| Tilt-down angle | a5 | 156 ° | 156 ° |
| External turning radius (over tyres) | Wa1 | 4.20 m | 13 ft 9 in |
| Articulation angle | a19 | 44 ° | 44 ° |
| Overall width less bucket | b1 | 2.29 m | 7 ft 6 in |
| Overall length - Less Bucket | l2 | 5.72 m | 18 ft 9 in |
| Standard tyres | | Alliance - A580 - 460/70 R24 159A8 | Alliance - A580 - 460/70 R24 159A8 |
| Ground clearance | m4 | 0.39 m | 1 ft 3 in |
| Performances | | | |
| Crowd | | 3.50 s | 3.50 s |
| Dump | | 2.70 s | 2.70 s |
| Engine | | | |
| Engine brand | | Deutz | Deutz |
| Engine model | | TCD 4.1 L4 | TCD 4.1 L4 |
| Engine norm | | Tier 4 | Tier 4 |
| Number of cylinders / Capacity of cylinders | | 4 - 4038 cm ³ | 4 - 246 in ³ |
| I.C. Engine power rating / Power (kW) | | 143 Hp / 105 kW | 143 Hp / 105 kW |
| Max. torque / Engine rotation | | 550 Nm / 2300 rpm | 406 ft/lbs / 2300 rpm |
| Engine cooling system | | 3 water radiators + air + hydraulic oil | 3 water radiators + air + hydraulic oil |
| Transmission | | | |
| Transmission type | | M-Varioshift | M-Varioshift |
| Max. travel speed (may vary according to applicable regulations) | | 40 km/h | 25 mi/h |
| Travel speed (laden) | | 40 km/h | 25 mi/h |
| Differential lock | | Limited slip differential on front and rear axles | Limited slip differential on front and rear axles |
| Parking brake | | Manual | Manual |
| Hydraulics | | | |
| Hydraulic pump type | | Variable displacement pump | Variable displacement pump |
| Hydraulic flow - Pressure | | 158 l/min / 270 bar | 42 US gpm / 3916 PSI |
| Tank capacities | | | |
| Hydraulic oil | | 150 l | 40 US gal |
| Fuel tank | | 150 l | 40 US gal |
| Diesel Exhaust fluid (AdBlue® type) | | 10 l | 3 US gal |
| Noise and vibration | | | |
| Noise at driving position (LpA) tested following NF EN 12053 norm | | 72 dB | 72 dB |
| Noise to environment (LwA) | | 107 dB | 107 dB |
| Vibration to whole hand/arm | | < 2.52 m/s ² | < 2.52 m/s ² |
| Miscellaneous | | | |
| Safety cab homologation | | Cabin ROPS - FOPS Level 2 | Cabin ROPS - FOPS Level 2 |



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend